CRAY VALLEY

Technical Data Sheet

Ricobond® 1731 HS

Powdered Maleinized Polybutadiene Dispersion

DESCRIPTION

Ricobond® 1731 HS is a low molecular weight, low vinyl butadiene functionalized with maleic anhydride, then dispersed on amorphous silica for ease in handling. It provides enhanced adhesion of rubber compounds to metal and textiles. The anhydride functionality can react with epoxy, amine, and hydroxyl groups, enabling the creation of unique adhesives, sealants, encapsulants, and coatings.

PRODUCT HIGHLIGHTS / PERFORMANCE PROPERTIES

Free flowing powder
Excellent reactivity Adhesion promoter
Compatibility with polar and non-polar materials
Moisture resistance
Low temperature tackifier
Reactive toughener for epoxies

Reactive compatibilizer for thermoplastics

SUGGESTED APPLICATIONS

Elastomers
Coatings
Electronics
Encapsulants
Sealants
Compatibilizers
Adhesives

TYPICAL PHYSICAL AND CHEMICAL PROPERTIES

Property		Value	Unit	
Molecular Weight (Mn)*		6,400	g/mol	
1,2 Vinyl Content*		28	wt. %	
Viscosity @ 45°C*		60,000	cps	
Tg*		-72	°C	
MA (Groups/Chain)*	Actives	9	-	
Specific Gravity @ 25°C		70	%	-
*Resin properties		1.3		

